

HT20-1 Mini Excavator

Hydraulic pilot operation



2ton with closed cabin



| HT20-1 | | Specification | |
|------------------------------------|------------------|-------------------------------|--------------|
| Engine | Laidong385 3TN25 | Working | 2000kg |
| Vavle | Beifang | Bucket capacity | 0.04m³ |
| Overall Dimension | | Rated power | 19KW/2200RPM |
| Total length/transportation length | 3337/2597mm | Revolution speed | 12RMP |
| Total width | 1100mm | Gradeability | 30° |
| Upper width | 1053mm | Working range | |
| Total Height | 2325mm | Max. Digging Height | 2580mm |
| Track width | 200mm | Max. Dumping Height | 1637mm |
| Track Gauge | 920mm | Max. digging depth | 2060mm |
| Mini. ground clearance | 119mm | Max. digging distance | 3130mm |
| Tailswing Radius | 1013mm | Min. swing Radius | 1575mm |
| Track ground length | 1050mm | Height when min. swing radius | 2075mm |
| Track length | 1545mm | | |

ACCESSORIES

•One Machine, multi-usage •Quick and easy replacement of accessories



Rotary quick hitch joint



Simple quick hitch



Hydraulic rotary quick change



200mm narrow bucket with teeth



600/800/1000mm Plain bucket



600/800/1000/1200mm Tilt Bucket



Hydraulic quick hitch



Semi-automatic hydraulic hitch



Log splitter



Grapple



Grapple



Hydraulic rotary grapple



Ripper



Auger



Break hammer



All-in-one hydraulic thumb clamp



Mechanical thumb clamp



Hydraulic thumb clamp



Grass trimmer



Root topper



Cropper



Sand bucket



Steel track



Rake



Fork



Trailer