

HT25 Mini Excavator

Retractable shoes, Boom swing, Tailless rotation



2.5ton with heater cabin

Machine Size		Performance Parameter	
Overall dimension (L*W*H)	3865mm*1050mm*2270mm	Standard bucket capacity	0.06m³
Axle base(Track length on ground)	1230mm	Swing speed	10~12 rpm
Track gauge	820mm	Max. Grade ability	35°
Min. Ground clearance	210mm	Max. Bucket digging force	14KN
Swing radius at tail	1125mm	Max. Arm digging force	10KN
Track System		Hydraulic system pressure	18Mpa
Maximum Travel speed	3.5km/h	Machine weight	2500kg
Width of track shoe(Rubber & steel track)	230mm	Working Range	
Number of track shoe per side(Steel track only)	38 pcs	Max. Digging height	3365mm
Number of upper roller/ bottom roller (per side)	0/4	Max. Dumping height	2385mm
Engine		Max. Digging depth	2050mm
Emission Standard	Euro 5/EPA	Max. Vertical digging depth	1725mm
Engine Brand / Power	Kubota D1105 14.2kw Perkins 14.7kw Laidong 3TE25 18.4Kw	Max. Digging radius	3860mm
Number of cylinder	3	Min .swing radius	1720mm
		Max. Lifting height of blade	230mm
		Max. Cutting depth of blade	275mm
		Boom swing angle(Left)	75°
		Boom swing angle(Right)	45°

ACCESSORIES

•One Machine, multi-usage •Quick and easy replacement of accessories



Rotary quick hitch joint



Simple quick hitch



Hydraulic rotary quick change



200mm narrow bucket with teeth



600/800/1000mm Plain bucket



600/800/1000/1200mm Tilt Bucket



Hydraulic quick hitch



Semi-automatic hydraulic hitch



Log splitter



Grapple



Grapple



Hydraulic rotary grapple



Ripper



Auger



Break hammer



All-in-one hydraulic thumb clamp



Mechanical thumb clamp



Hydraulic thumb clamp



Grass trimmer



Root topper



Cropper



Sand bucket



Steel track



Rake



Fork



Trailer