

HT22 Mini Excavator



Model: HT22				
Total length/transport length	4750mm	Operating weight	2172kg	
total width	990mm/1300mm	Bucket capacity	0.056m³	
Top Width	1050mm	Rated power	14.2KW/2200rpm	
Total height	2470mm	Rated speed	9.5r/min	
Track width	230mm	Gradeability	58%	
Track Gauge	780mm/1090mm	Engine	Model	KUBOTA D1105 3 cylinder direct injection
Min. ground clearance	150mm		Rated power	14.2KW/2200
Tail turning radius	780mm	Main valve	Model	TRM10-BX-09-JNJT-01
Track ground length	1200mm		Pressure	20.5MP
Track length	1500mm	Main valve	Model	TFA10VO28/53R
Max. digging height (a)	3500mm		Displacement	28ml/r
Max.unloading height(b)	2560mm	Traveling Motor	Model	KTD-490
Max Digging depth(c)	2370mm		Traveling speed	2.2/4.3km/h
Max. digging distance(d)	3030mm	Fuel tank	Traction	18KN
Min.turning radius(e)	1750mm		Capacity	21L
Max. height at minimum turning radius(f)	2600mm	Cooling system	Capacity	5.05L
		hydraulic oil tank	Capacity	21.4L

ACCESSORIES

•One Machine, multi-usage •Quick and easy replacement of accessories



Rotary quick hitch joint



Simple quick hitch



Hydraulic rotary quick change



200mm narrow bucket with teeth



600/800/1000mm Plain bucket



600/800/1000/1200mm Tilt Bucket



Hydraulic quick hitch



Semi-automatic hydraulic hitch



Log splitter



Grapple



Grapple



Hydraulic rotary grapple



Ripper



Auger



Break hammer



All-in-one hydraulic thumb clamp



Mechanical thumb clamp



Hydraulic thumb clamp



Grass trimmer



Root topper



Cropper



Sand bucket



Steel track



Rake



Fork



Trailer