

# HT18-1 Mini Excavator

KOOP 292F 2cylinder,KUBOTA D722 3cylinder



# HT18-3 Mini Excavator



Model:HT18-1			
Engine	KUBOTA D722,KOOP 292	Min.ground clearance	119mm
Mainvalve	BEIFANG	Tail turning radius	790mm
Working weight(kg)	1800kg	Track ground length	1050mm
Bucket capacity	0.03m <sup>3</sup>	Track length	1545mm
Power	10.2kw/14kw	Max digging height	2580mm
Swing speed	12RMP	Max.unloading height	1637mm
Gradeability	30	Max.digging depth	2060mm
Overall legnth	4325/1655mm	Max.digging distance	3160mm
Overall width	1100mm	Min.turning radiuse	1711mm
Upper width	990mm	Max.height at minimum turning radius	2048mm
Overall height	2272mm		
Standard track shoe width	200mm	Boom swing Angle(left)°	75
Track Gauge	920mm	Boom swing Angle(right)°	45

Model:HT18-3			
Engine	KUBOTA D722,KOOP 292	Min.ground clearance	119mm
Mainvalve	BEIFANG	Tail turning radius	790mm
Working weight(kg)	1800kg	Track ground length	1050mm
Bucket capacity	0.03m <sup>3</sup>	Track length	1545mm
Power	10.2kw/14kw	Max digging height	2580mm
Swing speed	12RMP	Max.unloading height	1637mm
Gradeability	30	Max.digging depth	2060mm
Overall legnth	4325/1655mm	Max.digging distance	3160mm
Overall width	1100mm	Min.turning radiuse	1711mm
Upper width	990mm	Max.height at minimum turning radius	2048mm
Overall height	2272mm		
Standard track shoe width	200mm	Boom swing Angle(left)°	75
Track Gauge	920mm	Boom swing Angle(right)°	45

# ACCESSORIES

•One Machine, multi-usage •Quick and easy replacement of accessories



Rotary quick hitch joint



Simple quick hitch



Hydraulic rotary quick change



200mm narrow bucket with teeth



600/800/1000mm Plain bucket



600/800/1000/1200mm Tilt Bucket



Hydraulic quick hitch



Semi-automatic hydraulic hitch



Log splitter



Grapple



Grapple



Hydraulic rotary grapple



Ripper



Auger



Break hammer



All-in-one hydraulic thumb clamp



Mechanical thumb clamp



Hydraulic thumb clamp



Grass trimmer



Root topper



Cropper



Sand bucket



Steel track



Rake



Fork



Trailer