

HT08 Mini Excavator

EPA/CE,ISO certificate Optional: Boom swing

Color can choose Red, Yellow, Blue, accept customization



Dimensions	
Total width	720-780mm
Total height	1300mm
Total length	2430mm
Min. ground clearance	80mm
Track ground length	1140mm
Track width	150mm

Performance Parameter			Working Range		
Model	HT08	Pump form	Single gear pump	Max.digging distance	2450mm
Rated power	7kw~7.5w	Set working pressure	14Mpa	Max.digging depth	1200mm
Bucket Capacity	0.025 m³	Swing speed	12 rpm	Max.digging height	2350mm
Bucket width	340mm	Travel speed	2.2Km/h	Max.dumping height	1600mm
Engine Model	KOOP 192F	Gradeability	30°	Min.Swing radius	1100mm
Optional Engine	BRIGGS&STRATTON	Ground pressure	19Kpa	Max. Upgrade height of bulldozer blade	120mm
Operating Weight	800 kg	Max. digging force	7.5KN	Max. Digging depth of bulldozer blade	200mm

ACCESSORIES

•One Machine, multi-usage •Quick and easy replacement of accessories



200mm narrow bucket with teeth



600/800/1000mm Plain bucket



600/800/1000/1200mm Tilt Bucket



Grapple



Grapple



Hydraulic rotary grapple



All-in-one hydraulic thumb clamp



Mechanical thumb clamp



Hydraulic thumb clamp



Sand bucket



Steel track



Rake



Rotary quick hitch joint



Simple quick hitch



Hydraulic rotary quick change



Hydraulic quick hitch



Semi-automatic hydraulic hitch



Log splitter



Ripper



Auger



Break hammer



Grass trimmer



Root topper



Cropper



Fork



Trailer